

## Description

*This unit is used for loading or of PCB, Specially use in limited workshop*

## Features

- User friendly 'soft touch' LED membrane control panel
- No PCB breakage guaranty because of special gas circuit design.
- Pneumatic clamps provided for magazine alignment.
- Top and bottom pneumatic clamps to secure magazine rack.
- High throughput with short magazine change-over time.
- Automatically diagnosing fault code display function.
- Durable cable and have long service life.
- Sturdy and stable design
- SMEMA compatible

## Technical specifications

- Transport height: 900mm  $\pm$  20mm.
- Transfer direction: L to R or specify R to L
- Power supply: 110V / 220V, 50 Hz/ 1 Ph, max 100VA
- Air supply & consumption:  $\geq$  6 bar, max 10 ltr/min.
- Pitch distance: 10.20.30.40mm pitch or specify.
- Time feed: 6 seconds Approx. Or specify.
- Magazine change-over time:  $\pm$  30 seconds
- Conveyor Speed: 0.5-20m/min adjustable
- Pitch distance: 10.20.30.40mm pitch or specify.
- Magazine storage: 50 pcs.



Model	Dimension (L*W*H.MM)	PCB size(MM)	Weight(KG)	Rack size(L*W*H.MM)
ELL250	1150*1150*1250	50*50-330*250	160KG	355*320*563
ELL330	1350*1350*1250	50*50-445*330	220KG	460*400*563
ELL390	1550*1550*1250	50*50-530*390	280KG	535*460*563

## Welcome inquiry

1, Please visit : [www.smtglobe.com](http://www.smtglobe.com)

2, Welcome to our factory in China

7, Looking forward to your email: [info@smtglobe.com](mailto:info@smtglobe.com)

8. Wechat/Whatsapp/skype: +86 13825296910