

Description

*This unit is used for unloading of PCBs from the production line.*

Features

Sturdy and stable design

Magazine quantity: upper 1pc, bottom 1pc.

Tank Replacement time: about 30 seconds or specify.

Step select: 10,20,30,40 mm or specify.

Spec. 110V or 220V, single phase max 250VA.

Barometric pressure from 4-6 bar, up to 10/min

Flexible platform to suit standard magazines.

Regulated pressure on attached pneumatic pusher.

Pusher position adjustable to center of the magazine.

User friendly "soft touch" LED membrane control panel.

SMEMA compatible

Dimension (L*W*H.MM)	PCB size(MM)	Weight(KG)	Rack size(L*W*H.MM)
1730*765*1250	50*50- 330*250	160KG	355*320*563
2065*845*1250	50*50- 445*330	220KG	460*400*563
2660*909*1250	50*50- 530*390	280KG	535*460*563
2660*970*1250	50x50- 530x460	320KG	535*530*563



## Welcome inquiry

1, Please visit : [www.smtglobe.com](http://www.smtglobe.com)

2, Welcome to our factory in China

7, Looking forward to your email: [info@smtglobe.com](mailto:info@smtglobe.com)

8. Wechat/Whatsapp/skype: +86 13825296910