

Description

PCB magazine loader is used for loading of PCBs from the production line.

Features

- Sturdy and stable design.
- PLC Program control.
- Selectable pitch settings.
- Automatic magazine change-over.
- Flexible platform to suit standard magazines.
- Regulated pressure on attached pneumatic pusher.
- Pusher position adjustable to center of the magazine.
- User friendly “soft touch” LED membrane control pane
- High throughput with short magazine change-over time
- SMEMA compatible.

Technical specifications

- Transport height: 900mm ±20mm.
- Transfer direction: L to R or specify R to L
- Belt type: ESD belt (round belt)
- Power supply: 110V /220V, 50 Hz/ 1 Ph, max 100VA
- Air supply& consumption: ≥6 bar, max. 10 ltr/min.
- Pitch distance: 10.20.30.40mm pitch or specify.
- Time feed: 6 seconds Approx. Or specify.
- Magazine change-over time: ±30 seconds
- Conveyor Speed: 0.5-20m/min adjustable
- Pitch distance: 10.20.30.40mm pitch or specify.
- Magazine storage: 50 pcs.



| Dimension (L*W*H.MM) | PCB size (MM) | Weight (KG) | Rack size (L*W*H.MM) |
|----------------------|---------------|-------------|----------------------|
| 1330*765*1250 | 50*50-330*250 | 140KG | 355*320*563 |
| 1650*845*1250 | 50*50-445*330 | 200KG | 460*400*563 |
| 1800*909*1250 | 50*50-530*390 | 240KG | 535*460*563 |
| 1800*970*1250 | 50*50-530*460 | 300KG | 535*530*563 |



Welcome inquiry

1, Please visit : www.smtglobe.com

2, Welcome to our factory in China

7, Looking forward to your email: info@smtglobe.com

8. Wechat/Whatsapp/skype: +86 13825296910