

Description

Wave solder outlet conveyor is used for transferring of PCBs/pallets into the soldering outlet.

Features

- Structure stability.
- Adjustable inclined angle
- Variable speed control to synchronize with wave soldering machine.
- Parallel and Smooth width adjustment. (lead screw)
- SMEMA compatible
- PLC controlled (optional)
- Cooling fans (optional)

Technical specifications

- Transport height: infeed: 1200mm \pm 20mm.
- outlet: 750 \pm 20mm
- Transfer direction: L to R or specify R to L
- Belt type: Green anti-static PVC belt or specify.
- Speed: 0.5-20m/min adjustable
- Power supply: AC 110 Volts Or 220 Volts; Single Phase
- Power consumption: 100VA max. or specify.
- Load bearing: 1.5kg/PCB.



Model	Dimension (L*W*H.MM)	PCB size (MM)	Weight (KG)	PCB Thickness
EWF-445	1200*600*1100	50*50-445*330	35KG	0.6~4 mm
EWF-530	1200*730*1100	50*50-530*460	45KG	0.6~4 mm



Welcome inquiry

1, Please visit : www.smtglobe.com

2, Welcome to our factory in China

7, Looking forward to your email: info@smtglobe.com

8. Wechat/Whatsapp/skype: +86 13825296910